



MOTOROLA

TWO-WAY RADIOS

GM340: The Popular Radio

The Popular Radio is the simple two-way radio solution for professionals who need to stay in contact. The GM340 can easily increase productivity by keeping users communicating, yet streamlines their radio use allowing them to concentrate on the job at hand. With the Popular Radio, communication couldn't be easier.



As Dedicated As You Are

Professional Radio

Operator friendly controls and features include:

- **Signalling**
The radio software encompasses Private Line™ and 5-tone selective signalling.
- **Voice Operated Transmit (VOX)**
Hands free operation when used with VOX accessory.
- **Emergency Signalling**
Sends help signal to a pre-defined person or group of people. The help signal can contain a pre-recorded voice message enabling your whereabouts or status to be determined immediately by the receiving person.
- **Lone Worker**
Added security and safety for individuals who work remotely from their team. The radio enters emergency mode if the user does not respond to the warning signal.
- **Option Board Expandability***
You can expand the existing capabilities by adding one of the following option boards:
 - *Mandown for added safety and security.*
 - *Voice Storage option board provides voice recorder features allowing you to store and retrieve messages.*
- **External Alarm**
Activates the vehicle horn and/or lights on receipt of an incoming call, so you won't miss a call even when away from your vehicle.
- **Public Address Mode**
This feature allows you to use your radio audio as a public address system simply by adding an external speaker and switch fitted and programmed by your dealer.
- **Data Capable**
A modem can be fitted inside a special expansion head, or external to the radio.

Additional features include:

- Channel Scan
- X-Pand™ Voice Compression and Low Level Expansion
- Adjustable Power Levels
- Programmable Channel Spacing (12.5/20/25 kHz)
- Talkaround
- Call Forward

*Please contact your Motorola dealer for further information.

GM340 Mobile Two-Way Radio Specifications

General		
Specification	VHF	UHF
Frequency Range:	136-174 MHz	403-470 MHz
Frequency Stability (-30°C to +60°C, 25°C Ref.)	±2.5 PPM	±2 PPM
Channel Capacity:	6	
Channel Spacing:	12.5/20/25 kHz	
Power Output:	1-25W	1-25W
Power Supply:	13.2Vdc (10.8 - 15.6 Vdc) negative vehicle ground	
Dimensions (L x W x H)	177mm x 176mm x 56mm (add 8mm for Volume Knob) (6.97" x 6.93" x 2.2" - add 0.3" for Volume Knob)	
Weight:	1400 g (3.15 lbs)	
Operating Temperature	-30 to 60°C	
Sealing	Passes rain testing to IP54	
Shock and Vibration	Meets MIL-STD 810-C,D&E and TIA/EIA 603	
Dust	Meets MIL-STD 810-C,D&E and TIA/EIA 603	
Humidity	Meets MIL-STD 810-C,D&E and TIA/EIA 603	

Transmitter	
Specification	VHF/UHF
Modulation Limiting:	±2.5 kHz @ 12.5 kHz ±4.0 kHz @ 20 kHz ±5.0 kHz @ 25 kHz
FM Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Conducted/Radiated Emissions:	-36 dBm < 1 GHz -30 dBm > 1 GHz
Adjacent Channel Power	-60 dB @ 12.5, -70 dB @ 20/25 kHz
Audio Response: (300 to 3000Hz)	+1, -3dB
Audio Distortion: @ 1000 Hz, 60% Rated Maximum Deviation:	3% Typical

Mobile Military Standards 810 C, D, & E						
Applicable MIL-STD	810C		810D		810E	
	Methods	Procedures	Methods	Procedures	Methods	Procedures
Low Pressure	500.1	1	500.2	2	500.3	2
High Temperature	501.1	1,2	501.2	1,2	501.3	1,2
Low Temperature	502.1	2	502.2	1,2	502.3	1,2
Temp. Shock	503.1	1	503.2	1	503.3	1
Solar Radiation	505.1	1	505.2	1	505.3	1
Rain	506.1	2	506.2	2	506.3	2
Humidity	507.1	2	507.2	2,3	507.3	3
Salt Fog	509.1	1	509.2	1	509.3	1
Dust	510.1	1	510.2	1	510.3	1
Vibration	514.2	8,10	514.3	1	514.4	1
Shock	516.2	1,2,5	516.3	1	516.4	1

Receiver		
Specification	VHF	UHF
Sensitivity (12dB SINAD): (ETS)	0.30µV (0.22 µV Typical)	
Intermodulation: (ETS)	>65 dB; >70 dB in Base Mode	
Adjacent Channel Selectivity: (ETS)	80dB @ 25 kHz 75dB @ 20 kHz 65dB @ 12.5 kHz	75 dB @ 25 kHz 70 dB @ 20 kHz 65 dB @ 12.5 kHz
Spurious Rejection: (ETS)	80 dB @ 20/25 kHz 75 dB @ 12.5 kHz	75 dB @ 20/25 kHz 70 dB @ 12.5 kHz
Rated Audio: (ETS)	3W Internal 7.5W & 13W External	
Audio Distortion @ Rated Audio:	3% Typical	
Hum and Noise:	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz	
Audio Response: (300 to 3000Hz)	+1, -3dB	
Conducted Spurious Emission per FCC Part 15:	-57 dBm <1 GHz -47 dBm >1 GHz	

*Availability subject to individual country's laws and regulations.

Specifications are subject to change without notice and are issued for guidance purposes only.

Radios meet applicable regulatory requirements.

Conforms to RTTE Directive: 1999/5/EC, 95/54/EC (72/245/EEC).

Relevant standards: EN300 086-2, EN300 113-2, EN301 489-05

Contact your local Authorised Motorola Dealer to find out more about how communicating with the Professional Radio series will benefit your organisation.

Özgül İletişim Telekomünikasyon Ltd.Şti.
Fethiye Sokak No:12/1 G.O.P. ANKARA - TR
Tel : +90 312 447 74 05 - Fax : +90 312 447 95 17

www.ozguliletisim.com

UK Sales Office

Middle East and Africa Headquarters:
Motorola Ltd
Jays Close, Viabes Industrial Estate
BASINGSTOKE, Hampshire
RG22 4PD United Kingdom
Tel: +44 1256 488093
Fax: +44 1256 488080

Central Europe

Headquarters:
Motorola GmbH
Geschäftsbereich Funk
Am Borsigturm 130
13507 BERLIN, Germany
Tel: +49 30 / 66 86-0
Fax: +49 30 / 66 86-18 09

Eastern Europe, Turkey and

Central Asia Headquarters:
Motorola GmbH
Heinrich Hertz Strasse 1
65232 TAUNUSSTEIN
Germany
Tel: +49 6128 700
Fax: +49 6128 951084



For exceptional performance, reliability and quality, Motorola Original accessories are the only options. For full details, please refer to the Professional Radio Series Accessories brochure.



MOTOROLA

Motorola, Professional Radios, As Dedicated As You Are and X-Pand are trademarks of Motorola Inc.

© 2004 Motorola, Printed in the United Kingdom
<http://www.motorola.com>